

HG60S ECONOMIC GLOSS METER

- 3.5 inch large screen with high resolution full-view display
- Display 3 sets of measurement data ,better for comparison
- Super configuration of hardware,integrated multiple innovative technologies
- Stable performance ,easy to read measure data
- Automatic calibration ,convenient and quick

3nh[®]
Focus on Color
www.3nh.com



HG series economic gloss meter is independently developed by 3nh ,with independent intellectual property ,manufactured according to ISO2813 and GB/T 9754. HG series with characteristic of larger display screen ,supply with high-end QC software ,stable performance ,high accuracy and easy to use .

HG60S ECONOMIC GLOSS METER

Gloss measurement so easy
with one-touch to complete!



SHENZHEN THREE NH TECHNOLOGY CO., LTD.


HG60S ECONOMIC GLOSS METER

PRODUCT FEATURES

- 1.60° angle for semi gloss
- 2.Concise appearance, feel good
- 3.Display 5 sets of measurement data, good for comparison
- 4.Built-in lithium ion rechargeable battery
- 5.Basic model measurement can meet basic glossiness testing requirements
- 6.One button for all angles measurement at the same location
- 7.Comply with international standards
- 8.Stable performance, easy to read data.



APPLICABLE INDUSTRIES



Automobile

Stonematerial

Plastic

Metal

Paints

Printing

Others

SPECIFICATION FEATURES

Measuring Angle:60°

Comply with standard: ISO 2813, GB/T 9754, ASTM D 523, ASTM D 2457

Measuring Area (mm):9x15

Measuring Range:0~200GU

Division Value:1GU

Measurement Range:0-200GU

Repeatability:±1GU

Reproducibility:± 1GU

Measurement Standard:Conform with JJG696 secondary class glossmeter working requirement

Chromaticity Corresponding:Corresponding with CIE 1931(2°) under CIE C light source **Errors:**±1.5 , ± 1.5%

Measuring Time:0.5s

Dimension:L*W*H : 160mm*75mm*90mm

Weight:350g

Language:Chinese/English

Battery:3200mAh Li-ion Battery, >10000 times(within 8 hours)

Display:TFT 3.5 inch

Interface:USB/RS-232

Operation Temperature:0~40°C(32~104°F)

Storage Temperature:-20~50°C(-4~122°F)

Humidity:<85% relative humidity, no condensation

Standard Accessories:Power Adapter, USB cable, User Manual, Calibration Plate

Optional Accessories:Miniature Printer



Shenzhen ThreeNH Technology Co., Ltd.

Address:F/6,Block5B,SkyworthInnoValley,Tangtou1stRoad,
Shiyan,BaoanDistrict,Shenzhen,P.R.China

Service Hotline: 400-666-2522 Email: 3nh@3nh.com

Tel: 86-0755-26508999

Fax: 86-0755-27190609